



DECLARATION OF PERFORMANCE

Nr 8.8/2023/ENG

According to the Annex III from Regulation (EU) No 305/2011

1. Unique identification code of the product type:

AquaSlab® 1212 – waterproof HDPE membrane type T

2. Intended use/es:

Damp proofing in buildings, including basement tanking

3. Manufacturer:

**Aqua Tech – Leja, Lietz Spółka jawna
Ul. Kineskopowa 1 bud. A lok. 26; 05-500 Piaseczno / Poland**

4. Authorised representative:

Not applicable

5. System/s of AVCP:

**System 2+
System 3 (reaction to fire)**

6a. Harmonised standard:

PN-EN 13967:2012

Notified body/ies:

**Polskie Centrum Badań i Certyfikacji S.A.
Entity No 1434**

7. Declared performance/s:

Essential characteristic	Levels and/or classes	Test method
Reaction to fire	class E	EN 13501-1
Watertightness	pass [watertight at 400 kPa]	EN 1928 method B
Tear resistance	longitudinal ≥ 600 N transverse ≥ 550 N	EN 12310-1
Joint strength	longitudinal joint ≥ 750 N/50 mm transverse joint ≥ 920 N/50 mm	EN 12317-2
Impact resistance	≥ 400 mm	EN 12691 method A
Tensile properties: - Maximum tensile force - Elongation	longitudinal ≥ 780 N/50 mm transverse ≥ 790 N/50 mm longitudinal ≥ 1100 % transverse ≥ 1100 %	EN 12311-2 method A
Resistance to static loading	≥ 20 kg	EN 12730
Durability: - Watertightness after artificial ageing - Watertightness after exposure to chemicals	pass [watertight at 400 kPa] pass [watertight at 400 kPa]	EN 1296 / EN 1928 EN 1847 / EN 1928
Dangerous substances	NPD	-

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Not applicable.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:



Marcin Lietz
Company partner
Aqua Tech – Leja, Lietz Spółka jawna

Piaseczno 11 April 2023
(place and date of issue)